

Standard Specifications

Housing	Extruded Steel Housing
Lens	UV Stabilized Dr Acrylic
Finish	Ultrachrome
Ballast	(ii) 120 Volt, 60Hz Electronic NPF Class P
Lamp(s)	Lamps are NOT included
UL Label	Damp Location

Custom Option Specifications

EMB2	Remote Battery Backup
ES	Energy Star
HB	High Power Factor
UNV	120-277 Volt, 50/60Hz Electronic HPF Class P

550 Series

P.O. Box 2083

Sanford, FL 32772

5481 Bryant Ave South
 Sanford, FL 32773

Phone 800.393.5630
 Fax 800.203.5698


www.ilighting.com
 sales@inconlighting.com

34Z
 Length 26.375"
 Width 6.50"
 Depth 9.00"

50Z
 Length 36.25"
 Width 6.50"
 Depth 9.00"

64Z
 Length 36.25"
 Width 6.50"
 Depth 9.00"

Ceiling or Wall Mount



Product Family	Lens Type	Finish	Wattage	Options
550	9-has two lenses, white on top/frosted on bottom	7- Ultrachrome	34Z- (2) F17 watt T8 (ii) 50Z- (2) F25 watt T8 (ii) 64Z - (2) F32 watt T8 (ii)	