

Standard Specifications	
Housing	Cold Rolled Steel Pan
Lens	Clear Ribbed or Frosted Acrylic
Frame	Cold Rolled Steel
Finish	Choose below
Ballast	(i) 120Volt/60HZ NPF Magnetic Class P (ii) 120Volt/60HZ NPF Electronic Class P (iii) 120-277Volt50/60HZ HPF Electronic Class P
Lamp(s)	Lamp(s) Included
UL Label	Damp Location

562 Series

P.O. Box 2083
Sanford, FL 32772

5481 Bryant Ave South
Sanford, FL 32773

Phone 800.393.5630
Fax 800.203.5698

www.ilighting.com
sales@inconlighting.com

Custom Option Specifications

27K	2700 Kelvin Lamp(s) (warm white)
35K	3500 Kelvin Lamp(s) (Daylight)
41K	4100 Kelvin Lamp(s) (cool white)
277v	277 Volts*
DIM	Dimming Ballast*
EMB1	Intergal Emergency Ballast (6.0" Depth)*
ES	Energy Star (indoor Only)*
FF	Flicker Free 13W (27K) Lamp(s)*
HB	High Power Factor *
PCH	Pullchain (120 volt only)

Replacement Parts


Lens-2901 | Replacement Polycarbonate Lens



562

Length 16.0"
Width: 5.0"
Depth: 4.25"

Wall or Ceiling Mount



Product Family	Lens Type	Finish	Wattage	Options
562	6- Frosted Ribbed 9- Clear Ribbed	0- Polished Brass 1-White 2- Brushed Nickle 3- Brushed Rust 3B-Bronze 4-Brushed Verde 5- Black 7- Ultra Chrome 8- Gold Pewter 9-Aged Brass	18- (2) 9 watt twin tube (i) 26- (2) 13 watt twin tube (i) 213QE- (2) 13 watt quad (ii) 36QE- (2) 18 watt quad (ii) 52QE- (2) 26 watt quad (iii) To ensure even illumination single lamping is not recommended for the 562 series.	

* Not Available in all wattages/ voltages consult factory