


712 Series




712



Diameter 15.25"
Depth 8.75"

Wall or Ceiling



Standard Specifications

Housing	Die-Cast Aluminum (Specify Finish)
Lens	Heat Treated Frosted Glass
Ballast	<i>i</i> 120 Volt/60Hz Magnetic NPF <i>ii</i> 120 Volt/60Hz Electronic NPF <i>iii</i> 120/277 Volt-50/60Hz Electronic HPF Fluorescent Cold Weather Start (-30°C) <i>iv</i> 120 Volt/60Hz Reactor Magnetic NPF <i>vi</i> 120/208/240/277 Volt-60Hz CWP Magnetic HPF
Lamp(s)	Lamp(s) Included
UL Label	↑Wet Location Listed

NOTE: All metal halide fixtures are IESA [pulse start] compliant

Custom Option Specifications

PE	Photocell (120 Volt Only)
PE2	Photocell (208-277V)
277	277 Volts*
EMB1	Emergency Ballast
EMB2	Remote Emergency Ballast
DIM	Dimming Ballast*
27K	27K Bulb
35K	35K Bulb
41K	41K Bulb
50K	50K Bulb
65K	65K Bulb
NL	No Lamps

Replacement Parts

LENS-712 | Replacement Frosted Glass


Available Finishes

-1
White



-3B
Bronze



Product Family	Lens Type	Housing	Wattage	Options*
712 	6 6 - Frosted	1 - White 3B - Bronze	26 - (2) 13 Watt Twin Tube (<i>i</i>)↑ 26QE - (1) 26 Watt Quad (<i>iii</i>)↑ 32TT - (1) 32 Watt Triple (<i>iii</i>)↑ 42TT - 42 Watt Triple (<i>iii</i>)↑ 52QE - (2) 26 Watt Quad (<i>iii</i>)↑ 64TT - (2) 32 Watt Triple (<i>iii</i>)↑ 70H - 70 Watt (HPS) (<i>iv</i>)↑ 70M - (1) 70 Watt MH (MED BASE) (<i>vi</i>)↑ 84TT - (2) 42 Watt Triple (<i>iii</i>)↑ 100H - 100 Watt (HPS) (<i>iv</i>)↑ 100M - 100 Watt (MH) (<i>vi</i>)↑ 150H - 150 Watt (HPS) (<i>iv</i>)↑ 150M - (1) 150 Watt MH (MED BASE) (<i>vi</i>)↑ 213QE - (2) 13 Watt Quad (<i>ii</i>)↑	PE - Photocell (120 Volt Only) PE2 - Photocell (208-277V) EMB1 - Emergency Ballast* (CFL Only) EMB2 - Remote Emergency Ballast (CFL Only) DIM - Dimming Ballast* 277 - 277 Volts*