

Standard Specifications

- Housing** Die-Cast Aluminum
Lens **76593** UV Stabilized Clear Polycarbonate
76893 Impact Resistant Borosilicate Glass
Ballast *i* 120 Volt/60Hz Magnetic NPF
ii 120 Volt/60Hz Electronic NPF
iii 120/277 Volt 50/60Hz Electronic HPF
Fluorescent Cold Weather Start (-30°C)
iv 120 Volt 60 Hz Reactor Magnetic NPF
v 120/208/240/277 Volt/60 Hz Magnetic HX HPF
vi 120/208/240/277 Volt/60 Hz Magnetic CWA HPF
 60 Hz CWA Magnetic HPF

NOTE: All metal halide fixtures are IESA [pulse start] compliant

- Lamp(s)** Lamp(s) Included
UL Label ⤴ Wet Location

765 Series



768 Series



-3B
Bronze




Custom Option Specifications

- PE** Photocell (120 Volt Only)
PE2 Photocell (208-277V)
EMB1 Emergency Ballast (CFL Only)
Cx Custom Wattage
277 277 Volts*
DIM Dimming Ballast*
EMB2 Remote Emergency Ballast
27K 27K Bulb
35K 35K Bulb
41K 41K Bulb
50K 50K Bulb
65K 65K Bulb
NL No Lamps

Replacement Parts


- LENS-7659** Replacement Clear Polycarbonate Lens
LENS-7689 Replacement Glass Lens

765 Series





Height 12.325"
 Width 12.325"
 Depth 9.0"

768 Series



Height 17.325"
 Width 16.50"
 Depth 8.0"

Wall

Product Family	Lens Type	Finish	Wattage	Options*
<p>765</p>  <p>768</p> 	<p>9</p> <p>9 - Clear Lens</p>	<p>3B</p> <p>3B - Bronze</p>	<p>765</p> <p>9 - (1) 9 Watt Twin Tube (i) ⤴ 13 - (1) 13 Watt Twin Tube (i) ⤴ 13QE - (1) 13 Watt Quad (ii) ⤴ 18 - (2) 9 Watt Twin Tube (ii) ⤴ 18QE - (1) 18 Watt Quad (ii) ⤴ 213QE - (2) 13 Watt Quad (ii) ⤴ 26 - (2) 13 Watt Twin Tube (i) ⤴ 26QE - (1) 26 Watt Quad (ii) ⤴ 32TT - (1) 32 Watt Triple (iii) ⤴ 42TT - (1) 42 Watt Triple (iii) ⤴ 36QE - (2) 18 Watt Quad (ii) ⤴ 84TT - (1) 84 Watt Triple (iii) ⤴ 52QE - (2) 26 Watt Quad (iii) ⤴ 50H - (1) 50 Watt HPS (MED) (iv) ⤴ 70H - (1) 70 Watt HPS (MED) (iv) ⤴ 100H - (1) 100 Watt HPS (MED) (iv) ⤴ 150H - (1) 150 Watt HPS (MED) (iv) ⤴ 50M - (1) 50 Watt MH (MED) (iv) ⤴ 70M - (1) 70 Watt MH (MED) (iv) ⤴ 100M - (1) 100 Watt MH (MED) (iv) ⤴ 150M - (1) 150 Watt MH (MED) (iv) ⤴ 175M - (1) 175 Watt MH (MED) (iv) ⤴</p>	<p>768</p> <p>175M - (1) 175 Watt MH (MOG) (vi) ⤴ 250M - (1) 250 Watt MH (MOG) (vi) ⤴ 400M - (1) 400 Watt MH (MOG) (vi) ⤴ 250H - (1) 250 Watt HPS (MOG) (vi) ⤴ 400H - (1) 400 Watt HPS (MOG) (vi) ⤴</p> <p>PE - Photocell (120V Only) PE2 - Photocell (208V-277V) EMB1 - Emergency Ballast* (CFL Only) EMB2 - Remote Emergency Ballast DIM - Dimming Ballast* 277 - 277 Volts*</p>