

### Standard Specifications

<b>Housing</b>	Impact Resistant Polycarbonate
<b>Lens</b>	UV Stabilized Frosted Acrylic
<b>Ballast</b>	<i>i</i> 120 Volt/60Hz Magnetic NPF <i>ii</i> 120 Volt/60Hz Electronic NPF <i>iv</i> 120 Volt/60Hz Magnetic Reactor NPF
<b>Lamp(s)</b>	Lamp(s) Included (CFL Only)
<b>UL Label</b>	↑Wet Location Listed

### 85565 Series

Black/Frosted




### Custom Option Specifications

<b>Cx</b>	Custom Wattage
<b>27K</b>	27K Bulb
<b>35K</b>	35K Bulb
<b>41K</b>	41K Bulb
<b>50K</b>	50K Bulb
<b>65K</b>	65K Bulb
<b>NL</b>	No Lamps

### Replacement Parts


**LENS-8556** | Replacement 4 Panel Frosted Lens

### Available Finishes



Height 17.125"  
Width 13.125"

Pole Mount



Product Family	Lens Type	Finish	Wattage	Options*
855	<b>6</b> 6 - Stabilized Acrylic	1 - White† 5 - Black	<b>INC</b> - 100 Watt Max Incandescent ■ <b>9</b> - (1) 9 Watt Twin Tube ( <i>i</i> ) <b>13</b> - (1) 13 Watt Twin Tube ( <i>i</i> ) <b>13QE</b> - (1) 13 Watt Quad ( <i>ii</i> ) <b>18</b> - (2) 9 Watt Twin Tube ( <i>ii</i> ) <b>18QE</b> - (1) 18 Watt Quad ( <i>ii</i> ) <b>26</b> - (2) 13 Watt Twin Tube ( <i>i</i> ) <b>213QE</b> - (2) 13 Watt Quad ( <i>ii</i> ) <b>26QE</b> - (1) 26 Watt Quad ( <i>iii</i> ) <b>32TT</b> - (1) 32 Watt Triple ( <i>iii</i> ) <b>36QE</b> - (2) 18 Watt Quad ( <i>ii</i> ) <b>65C</b> - (1) 65 Watt (CFL) ( <i>ii</i> ) <b>50H</b> - (1) 50 Watt HPS (MED) ( <i>iv</i> ) <b>70H</b> - (1) 70 Watt HPS (MED) ( <i>iv</i> )	

†Additional lead times may apply.  
■ - Bulb Not Included.

↑-UL Wet Location Listed